

Donner II. JAKOST AutoFlow 01

VYSTAVENO/ROZBALENO - více informací v popisu



EAN: 8596220009289x

3 419 Kč

2 826 Kč bez DPH

II. Jakost

SKLADEM pouze 1 ks - ROZBALENO - mohou být mírné oděrky. Originál obal může být poškozen nebo chybí

AutoFlow 01 is characterized by a simple functionalist design that perfectly stands out in modern washrooms with a clean design.

Simple to use.

The use of automatic faucets is very convenient. Simply place your hands near the faucet in the sink, the infrared sensor detects their presence and automatically activates the flow of water. After finishing washing, the sensor automatically stops the flow of water (after 1.5 seconds). The water temperature can be adjusted using the mixing lever on the right side. For safety reasons, the faucet is equipped with an automatic shut-off function after a few minutes of continuous operation.

Water savings up to 60%.

Water escaping from the automatic faucet passes through a aerator which aerates it and reduces its flow. Thanks to touchless control, it ensures that water from the faucet flows only when you actually need it. The combination of these two technologies results in water savings of 30-60 percent compared to a

regular water tap.

Sanitary operation.

The fact that the battery operation is completely contactless prevents cross-contamination. Contactless batteries are used in food establishments, medical facilities, and high-traffic toilets to maintain a high standard of hygiene. The supply hoses are equipped with an additional valve with a filter to prevent the backflow of cold and hot water in the plumbing. Contactless jet dryers and hot air dryers Jet Dryer are excellent complements to DONNER AutoFlow automatic faucets.

Safe battery power.

The automatic water tap is powered by four standard pencil batteries inserted into a casing located directly inside the battery. No power cable needs to be connected and there is no risk of electric shock. With the use of quality alkaline batteries, the lifespan can reach up to one year with 200 uses per day. In case the batteries run out, the water will remain closed.

Quality materials

The body of the contactless AutoFlow 01 battery is made of brass. Its robust design guarantees a long lifespan even in highly busy operations. The entire surface of the battery is chrome-plated for easy maintenance.

Parts of the packaging:

- Assembly instructions
- Automatic battery
- 2x 50cm armored hose 3/8"
- 2x check valve with strainer 3/8" to 1/2"
- Battery adapter including holder
- Bag with components (nut, sealing, washer, screw)

Parameters

Basic parameters

Model:	Donner AutoFlow 01
Warranty:	2 years

Technical parameters

Material:	Brass-plated
Boot system:	Automatic infrared
Switching distance:	6-30 cm automatic calibration
Appropriate water temperature:	0-80 °C
Operating temperature:	0-45 °C
Armoured hoses:	2x 50cm 3/8" + reducing adapter with non-return valve 3/8" to 1/2"
Coarse dirt filter.:	Yes (sieve)

Electric specifications

Power:	Battery adapter 4x AA 1.5 V
--------	-----------------------------

Protective and security elements

Degree of protection:	IP56
Automatic water shut-off:	Yes

Dimensions, weight, packaging

Device dimensions:	200 x 120 x 53 mm (including handle 76 mm) (L/W/H)
Device weight:	1 kg
Packaging dimensions:	135 x 330 x 240 mm (w/l/h)
Weight including packaging (kg):	1.9 kg
Packing method:	Protective polybag, polystyrene cover, cardboard box
Width of the packaging (cm):	26.5
Height of packaging (cm):	26.5
Depth of packaging (cm):	18.5

