Donner AutoFlow 03

Bezkontaktní baterie zajistí vysoký hygienický standard na místech jako jsou nemocnice, zdravotnické zařízení, apod.



EAN: 8596220009302 **3 799 Kč** 3 140 Kč bez DPH

AutoFlow 03 is characterized by an elegant clean rounded design.

Simple to use.

The usage is very simple. After placing your hands in the sink, the water flow will start automatically. After finishing washing and moving your hands away from the sensor, the water flow will start automatically. You can adjust the water temperature using the mixing lever on the right side of the faucet. The faucet will automatically turn off the water flow after a few minutes of continuous operation.

Water savings up to 60%.

In the head of the battery, there is a aerator that aerates the flowing water and effectively regulates its flow.

Thanks to the infrared sensor, the water flows only when you need it. Thanks to the aerator and the sensor, the water consumption is lower by 30-60 percent compared to a regular faucet.

Sanitary operation.

Completely touchless use prevents cross-contamination with bacteria and viruses. The operation is therefore very hygienic. Touchless faucets ensure a high hygiene standard in places such as hospitals, medical facilities, food establishments, and high-traffic areas. The supply hoses are equipped with an additional valve with a strainer to prevent backflow of cold and hot water in the pipes. The ideal complement to automatic faucets are touchless jet and hot air hand dryers Jet Dryer.

Safe battery power.

The Donner AutoFlow 03 faucet is powered by 4 AA batteries located in a compartment under the sink. This eliminates any issues with power cables. Additionally, the use is completely safe. In case the batteries run out, the faucet will remain closed. When using high-quality alkaline batteries, the battery life can last up to one year with 200 activations per day.

Quality materials

The body of the contactless battery AutoFlow 03 is made of brass. Its robust design guarantees long lifespan even in highly demanding conditions. The entire surface of the battery is chrome-plated for easy maintenance.

Parts of the packaging:

- Assembly instructions
- Automatic battery
- 2x 50cm armored hose 1/2"
- 2x backflow valve with strainer 1/2"
- Battery adapter including holder
- Bag with components (nut, sealing, washer, screw)

Parameters

Basic parameters	
Model:	Donner AutoFlow 03
Warranty:	2 years
Product TARIC code:	84818090
Technical parameters	
Material:	Brass-plated
Boot system:	Automatic infrared
Switching distance:	6-30 cm automatic calibration
Appropriate water temperature:	0-80 °C
Operating temperature:	0-45 °C
Armoured hoses:	2x 50cm 1/2" + 2x 1/2" check valve
Coarse dirt filter.:	Yes (sieve)
Electric specifications	
Power:	Battery adapter 4x AA 1.5 V
Protective and security elements	
Degree of protection:	IP56
Automatic water shut-off:	Yes
Dimensions, weight, packaging	
Device dimensions:	180 x 190 x 61 mm (including handle 75 mm) (height/width/depth)
Device weight:	1.3 kg
Packaging dimensions:	135 x 330 x 240 mm (w/l/h)
Weight including packaging (kg):	2 kg
Packing method:	Protective polybag, polystyrene cover, cardboard box
Width of the packaging (cm):	26.5
Height of packaging (cm):	10.5
Depth of packaging (cm):	18.5

