

EcoMaster II. JAKOST HEAVY DUTY Plus

VYSTAVENO/ROZBALENO - více informací v popisu



EAN: 8596220000033x

5 347 Kč

4 419 Kč bez DPH

II. quality

We offer 2 pieces of crushers in second quality. UNPACKED, may have slight scratches. Original packaging is damaged.

Food waste disposer is recommended for all households. It optimally combines all parameters and improvements typical for more luxurious models.

Compared to the cheaper STANDARD model, it has a larger and deeper grinding chamber, overall motor and chamber insulation, including insulation filling.

It also includes a waste bend with an inlet for potential connection of the sink overflow and an improved plug for filling the sink made of high-quality stainless steel with sealing, including a plastic longitudinal handle.

Surface treatment of the neck - polished matte stainless steel with the EcoMaster logo.

Welt Servis Ltd. holds products and spare parts in stock and provides warranty and post-warranty service and professional installations for households and catering establishments throughout the Czech Republic.

Parts of the packaging:

- Assembly instructions
- Removable rubber cuff
- Waste bend with additional inlet for overflow / dishwasher including flange and screws.
- Plug made of high-quality stainless steel with seal including a plastic handle.

Parameters

Basic parameters

Model:	EcoMaster HEAVY DUTY Plus
Use:	Powerful model for demanding users
Warranty:	4 years
Product TARIC code:	85098000

Technical parameters

Mounting method - installation:	Hanging under the sink
Sink flange clamping system:	EZ Mount
Sink flange material:	Plastic (Flanged Flange)
Housing material - case:	ABS plastic
Surface finish - color:	White lacquer finish
Boot system:	Pressure air switch, button
Size of the chamber:	L
Grinding segments:	Stainless steel, reinforced blades
Grinding ring:	36 arch holes, projections
Bearings:	Bronze, self-lubricating
Protective cushion:	Removable splash guard
Sink drain hole:	Ø 9cm (3.5 ")
Maximum sink thickness:	15 mm (at clamping point)
Dishwasher / washing machine connection, sink overflow:	Yes
Soundproofing:	Engine and grinding chamber cover + insulating filler
Average water consumption:	10 l / running 3x a day approx

Electric specifications

Input voltage:	AC 220-240 V
Frequency:	50/60 Hz
Performance:	3/4 HP (550 W)
Current consumption:	2.25 A
Motor type:	Commutator DC
Engine speed:	2700 rpm
Torque:	1.8 Nm
Power cable:	CEE plug 7/7
Power cord length:	140 cm

Dimensions, weight, packaging

Device weight:	4,7 kg
Device dimensions:	413x167x167 mm (h/w/d)
Packaging dimensions:	475x230x230 mm (h/w/d)
Packing method:	Protective polybag, polystyrene cover, cardboard box
Width of the packaging:	23 cm
Height of the packaging:	47.5 cm
Depth of the packaging:	23 cm
Weight including packaging (kg):	5.6

Protective and security elements

Resettable thermal fuse:	Yes, reset via fuse button
Short circuit protection:	Yes
Interference filter:	Yes, it meets EMC-electromagnetic standards. compatibility
Electricity class protection:	I. (protective conductor)

