

Jet Dryer STORM

Voda je z rukou nejen vysoušena, ale také stírána. Snadná montáž. Tzv. antivandal úprava (v kovovém provedení)



EAN: 8596220006387
4 090 Kč
3 380 Kč excluding VAT



EAN: 8596220006370
3 490 Kč
2 884 Kč excluding VAT



EAN: 8596220006394
4 090 Kč
3 380 Kč excluding VAT



EAN: 8596220012357
4 090 Kč
3 380 Kč excluding VAT

STORM represents a combination of compact dimensions of hot air heaters with the drying power of jet dryers. The robust metal construction is suitable even for highly frequented places. Simply install the dryer on the wall and forget about it, no more buying paper towels, no more overflowing bins.

Welt Servis spol. s r.o. keeps products and spare parts in stock and provides both warranty and post-warranty [service](#).

The nozzle in the shape of a blade

The warm air comes out of the dryer through a narrow elongated nozzle. This way, water is not only dried, but also wiped off hands. The drying process is similar to that of large jet dryers.

The air is drawn into the dryer from the bottom side of the dryer through the dust filter.

Constant temperature throughout the drying process

You don't have to wait long seconds for the dryer to heat up to full power. The Storm reaches operational temperature practically immediately after inserting your hands.

Easy installation

Installation on the wall is done using four screws. Any service or filter replacement is quick and easy. The rear cover of the dryer just needs to be snapped off, you don't have to unscrew anything.

Antivandal adjustment (in metal adjustment)

The metal cover of the dryer is made from a single piece. A 2-millimeter thick sheet resists any vandalism. The surface finish allows for easy maintenance, the dryer only needs to be wiped with a damp cloth. The cover is resistant to damage from a clumsily discarded cigarette.

Parts of the packaging:

- Assembly instructions
- Allen key
- 5 x 25 mm self-tapping screw, 4 pieces.
- 5 mm anchor 4 pieces.

Parameters

Basic parameters

Model:	JetDryer STORM
Use:	Suitable for all types of operations
Product TARIC code:	85163300
Warranty:	3 years

Technical parameters

Mounting method - installation:	Wall
Noise - sound level:	78 dB
Surface finish - color:	White plastic / white lacquer / brushed stainless steel
Controls:	No
Status indication:	No
Boot system:	Automatic- infrared
Trigger distance:	15-20 cm
Warm air:	Yes
Air flow:	23.5 l / s
Air Speed:	85 m / s
UV sterilization:	No
Type:	hot air
Case material:	White metal: Metal, White ABS plastic: ABS Plastic, Matte stainless steel: Stainless Steel, Black metal: Metal
Standard air filter:	Yes- filter cartridge

Protective and security elements

Overcurrent protection, overheating and short-circuit protection:	Yes
Electricity class protection:	I. (protective conductor)
Degree of protection:	IP23

Electric specifications

Input voltage:	AC 220-240 V
Frequency:	50/60 Hz
Power input:	1800 W
Heating element output:	1250 W
Motor power:	550 W
Motor type:	Serial AC commutator
Current consumption:	7.8 A
Standby mode:	<2 W
Power cable:	CEE plug 7/7
Power cord length:	90 cm

Dimensions, weight, packaging

Device dimensions:	291x221x152 mm (h / w / d)
Device weight:	White metal: 3.84, White ABS plastic: 3.25, Matte stainless steel: 3.6, Black metal: 3.84
Packaging dimensions:	350x270x220 mm (h / w / d)
Weight including packaging (kg):	White metal: 4.1, White ABS plastic: 3.5, Matte stainless steel: 3.84, Black metal: 4.1
Packing method:	Protective polybag, polystyrene cover, cardboard box
Width of the packaging (cm):	27
Height of packaging (cm):	35

Depth of packaging (cm):

22

